

Priloga 1: normalno nadvišanje v krožnem loku

R	HITROST v (km/h)																											R		
(m)	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140	145	150	155	160	(m)		
6000																		20	20	20	20	20	25	25	25	30	30	6000		
5000																20	20	20	20	20	25	25	30	30	30	35	35	5000		
4000														20	20	20	20	25	25	30	30	30	35	35	40	45	45	4000		
3000											20	20	20	20	25	25	30	30	35	35	40	45	45	50	55	55	60	3000		
2500										20	20	20	25	25	30	30	35	40	40	45	50	50	55	60	65	70	75	2500		
2000									20	20	25	25	30	30	35	40	45	45	50	55	60	65	70	75	80	85	90	2000		
1900								20	20	20	25	25	30	35	35	40	45	50	55	60	65	70	75	80	85	90	95	1900		
1800								20	20	20	25	30	30	35	40	45	50	50	55	60	65	70	75	85	90	95	100	1800		
1700							20	20	20	25	25	30	35	40	40	45	50	55	60	65	70	75	80	90	95	100	105	1700		
1600							20	20	20	25	30	30	35	40	45	50	55	60	65	69	75	80	85	95	100	105	115	1600		
1500							20	20	25	25	30	35	40	45	45	50	55	65	70	75	80	85	95	100	105	115	120	1500		
1400						20	20	20	25	30	30	35	40	45	50	55	60	65	75	80	85	90	100	105	115	120	130	1400		
1300						20	20	25	25	30	35	40	45	50	55	60	65	70	80	85	90	100	105	115	125	130	140	1300		
1200						20	20	25	30	35	40	45	50	55	60	65	70	80	85	90	100	110	115	125	135	140	150	1200		
1100					20	20	25	25	30	35	40	45	50	60	65	70	80	85	95	100	110	120	125	135	145			1100		
1000					20	20	25	30	35	40	45	50	60	65	70	80	85	95	100	110	120	130	140	150				1000		
900				20	20	25	30	35	40	45	50	55	65	70	80	85	95	105	115	125	135	145						900		
800				20	20	25	30	40	45	50	55	65	70	80	90	100	105	115	130	140	150							800		
700			20	20	25	30	35	45	50	55	65	75	80	90	100	110	125	135	145									700		
600			20	25	30	35	45	50	60	65	75	85	95	105	120	130	145											600		
550		20	20	25	30	40	45	55	65	75	85	95	105	115	130	140												550		
500		20	25	30	35	45	50	60	70	80	90	105	115	130	140													500		
450		20	25	30	40	50	55	65	75	90	100	115	130	140														450		
400	20	20	30	35	45	55	65	75	85	100	115	130	145															400		
350	20	25	30	40	50	60	75	85	100	115	130	145																350		
300	20	30	40	50	60	70	85	100	115	135	150																	300		
275	25	30	40	50	65	80	85	110	125	145										h=7,1.V²/R										275
250	25	35	45	60	70	85	100	120	140																			250		
225	30	40	50	65	80	95	115	135																				225		
200	30	45	55	70	90	105	130	150																				200		
180	35	50	65	80	100	120	140																					180		