

Priloga 2: Minimalno nadvišanje v krožnem loku.

R	HITROST v km/h																												R
(m)	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140	145	150	155	160	(m)	
6000																													6000
5000																													5000
4000																													4000
3000																													3000
2500																													2500
2000																									20	30	40	2000	
1900																								20	25	35	45	1900	
1800																							20	25	35	45	55	1800	
1700																						20	25	35	45	55	65	1700	
1600																						20	30	40	55	65	75	1600	
1500																					20	30	40	50	65	75	90	1500	
1400																			20	30	40	50	65	75	90	105	1400		
1300																			20	30	40	55	65	80	90	105	120	1300	
1200																		20	30	40	55	65	80	95	110	125	140	1200	
1100																	20	30	40	55	70	80	100	110	130	145		1100	
1000																20	30	45	55	70	85	100	120	135	150			1000	
900															20	30	45	60	75	90	110	125	145					900	
800														20	35	50	65	80	100	120	135							800	
700													25	40	55	75	90	110	130	150								700	
600											20	30	45	65	85	105	125	145										600	
550											25	40	60	80	100	125	145											550	
500										20	40	60	60	100	125	150												500	
450									20	35	55	75	100	125	150													450	
400									30	55	75	100	125															400	
350								25	50	75	105	130																350	
300							25	50	80	110	140																	300	
275						20	40	65	100	130								hmin=11,8V2/R-115											275
250						30	55	85	115	150																		250	
225					70	45	75	105	140									b = 0,75 m/s²											225
200					35	65	100	135																				200	
180				20	50	85	120																					180	